

## ■ Model No. **PNST-10 / PNST-10M**

Weight : 7.6 kgs

### ■ Punching Capacity:

- Max. Thickness:  
Stainless Steel : 1.6 mm  
Mild Steel : 3.2 mm
- Max. Diameter : 4 inch
- 4 inch diameter hole on 3.2 mm thickness mild steel

### ■ Features:

- Suitable to punch holes in electrical panels, switchboards and others.
- Single action cylinder with spring release.
- Fast, easy, and simple to operate.
- Compact design makes this a perfect choice for use on construction sites and maintenance jobs.
- Powerful 12.7 ton hydraulic ram.



## ■ Accessories:

Model No.	Accessories	
PNST-10	<ul style="list-style-type: none"> <li>• HP-180N</li> <li>• PDV-10</li> <li>• Draw Stud (3/4", 3/8")</li> <li>• Spacer (S, M, L)</li> <li>• Plastic Case</li> </ul>	6 Punch Die Sets: 1/2", 3/4", 1", 1-1/4", 1-1/2", 2"
PNST-10M	<ul style="list-style-type: none"> <li>• HP-180N</li> <li>• PDV-10</li> <li>• Draw Stud (3/4", 3/8")</li> <li>• Spacer (S, M, L)</li> <li>• Plastic Case</li> </ul>	6 Punch Die Sets: 16mm, 20mm, 25mm, 32mm, 40mm, 50mm

- Do not use HP-180N with any compression head that requires a relief valve to ensure a constant compression.

## ■ Punch Driver : PDV-10

Ram Stroke : 25 mm  
 Oil Required : 47 cc  
 Max. Output : 12.7 tons / 125 kN

## ■ Packaging :

plastic carrying case

